(in accordance with Regulation (EU) 2015/830)

APSA GREASE MOLY



SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: APSA GREASE MOLY

1.2 Relevant identified uses of the mixture and uses advised against.

Lubricant Grease

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: AMALIE PETROQUIMICA / APSA

Address: C/ Príncipe de Vergara 128

 City:
 Madrid

 Province:
 28002 Madrid

 Telephone:
 0034 915 644 778

Fax:

E-mail: apsa@amaliepetroquimica.com Web: www.amaliepetroquimica.com

1.4 Emergency telephone number: 0034 915 644 778 (Only available during office hours; Monday-Friday; 09:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008: Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:

H statements:

H412 Harmful to aquatic life with long lasting effects.

P statements:

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with the legislation in force.

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

Distillates (petroleum), solvent-dewaxed heavy parafinic Distillates (petroleum), hydrotreated heavy naphthenic

(in accordance with Regulation (EU) 2015/830)

APSA GREASE MOLY

 Version: 9
 Page 2 of 9

 Revision date: 25/07/2018
 Print date: 29/11/2018



Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

| | | | (*)Classification No 127 | |
|--|--|---------------|---|------------------------------------|
| Identifiers | Name | Concentrate | Classification | specific concentration limit |
| Index No: 649-474- 00-6 CAS No: 64742-65-0 EC No: 265-169-7 Registration No: 01- 2119471299-27-XXXX | [1] A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100°F (19cSt at 40°C).,Baseoil - unspecified,Distillates (petroleum), solvent-dewaxed heavy paraffinic | 25 - 49.99 % | - | - |
| Index No: 649-465- 00-7 CAS No: 64742-52-5 EC No: 265-155-0 Registration No: 01- 2119467170-45-XXXX | [1] A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains relatively few normal paraffins.,Baseoil - unspecified,Distillates (petroleum), hydrotreated heavy naphthenic | 25 - 49.99 % | - | - |
| CAS No: 7782-42-5 EC No: 231-955-3 Registration No: 01- 2119486977-12-XXXX | [1] Graphite | 2.5 - 9.99 % | - | - |
| CAS No: 1330-78-5 EC No: 215-548-8 Registration No: 01- 2119531335-46-XXXX | tris(methylphenyl) phosphate | 0.25 - 2.49 % | Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Repr. 2, H361fd | - |
| CAS No: 115-86-6 EC No: 204-112-2 Registration No: 01- 2119457432-41-XXXX | [1] triphenyl phosphate | 0 - 0.249 % | Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 1, H410 (M=1) | - |

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

^[1] Substance with a Community workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2015/830)

APSA GREASE MOLY



If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

The contaminated area should be immediately cleaned with an appropriate de-contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

(in accordance with Regulation (EU) 2015/830)

APSA GREASE MOLY



Version: 9 Page 4 of 9
Revision date: 25/07/2018 Print date: 29/11/2018

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills. The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Profesional use only. Automotive, Industry, Transport, Off-Highway Machinery.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

| A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100°F (19cSt at 40°C). Baseoil - unspecified, Distillates (petroleum), solvent-dewaxed heavy paraffinic A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains relatively few normal paraffins., Baseoil - unspecified, Distillates (petroleum), | Name | CAS No. | Country | Limit value | ppm | mg/m³ |
|--|--|------------|-------------|-------------|-----|---------------------------------------|
| hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains relatively few normal paraffins.,Baseoil - | hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100°F (19cSt at 40°C).,Baseoil - unspecified,Distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-65-0 | España [1] | | | 10 |
| petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains relatively few normal paraffins.,Baseoil - | | | | Eight hours | | 5 |
| hydrotreated heavy naphthenic | petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains relatively few normal paraffins.,Baseoil - unspecified,Distillates (petroleum), | 64742-52-5 | España [1] | Short term | | 10 |
| Fspaña [1] Eight hours (Fracción | Graphite | 7782-42-5 | España [1] | | | 2 (polvo) (Fracción respirable) |
| United Eight hours 2 | | | United | | | 2 |
| Kingdom [2] Short term | | | Kingdom [2] | Short term | | |
| España [1] Eight hours 3 | | | España [1] | | | 3 |
| trinhenyl phosphate 115-86-6 Snort term | triphenyl phosphate | 115-86-6 | | | | |
| United Kingdom [2] Short term 6 | | | | _ | | |

^[1] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT) para el año 2017.

^[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

| Name | DNFI /DMFI | Tyne | Value | |
|------|------------|------|-------|--|

(in accordance with Regulation (EU) 2015/830)

APSA GREASE MOLY

 Version: 9
 Page 5 of 9

 Revision date: 25/07/2018
 Print date: 29/11/2018

| Graphite CAS No: 7782-42-5 EC No: 231-955-3 | DNEL (Workers) | Inhalation, Long-term, Local effects | 1,2 (mg/m³) |
|---|-------------------|---|-----------------|
| tris(methylphenyl) phosphate CAS No: 1330-78-5 EC No: 215-548-8 | DNEL (Workers) | Inhalation, Long-term, Systemic effects | 0,47 (mg/m³) |
| triphenyl phosphate CAS No: 115-86-6 EC No: 204-112-2 | DNEL (Workers) | Inhalation, Long-term, Systemic effects | 0,55 (mg/m³) |

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable

minimum.

Distillates (petroleum), solvent-dewaxed heavy parafinic Distillates (petroleum), hydrotreated heavy naphthenic

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

| Concentration: | 100 % | | | | |
|--|---|--|--|--|--|
| Uses: | Lubricant Grease | | | | |
| Breathing protection: | | | | | |
| If the recommended technical measures are observed, no individual protection equipment is necessary. | | | | | |
| Hand protection: | | | | | |
| If the product is har | ndled correctly, no individual protection equipment is necessary. | | | | |
| Eye protection: | | | | | |
| PPE: Characteristics: | Protective goggles against particle impacts. «CE» marking, category II. Eye protector against dust and smoke. | | | | |
| CEN standards: | EN 165, EN 166, EN 167, EN 168 | | | | |
| Maintenance: | Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. | | | | |
| Observations: | Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc. | | | | |
| Skin protection: | | | | | |
| PPE: | Work footwear. | | | | |
| Characteristics: | «CE» marking, category II. | | | | |
| CEN standards: | EN ISO 13287, EN 20347 | | | | |
| Maintenance: | This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. | | | | |
| Observations: | Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident | | | | |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Paste with characteristic colour and odour

Colour: Black Odour:Mild, EP

Odour threshold: N.A./N.A.

pH:N.A./N.A.

Melting point: N.A./N.A. Boiling Point: >250 °C Flash point: >210 °C Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:N.A./N.A.

(in accordance with Regulation (EU) 2015/830)

APSA GREASE MOLY



Relative density:0.900 Solubility:Oil solvents Liposolubility: N.A./N.A. Hydrosolubility: Insoluble

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A. Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information. Dropping point: > 180°C

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

(in accordance with Regulation (EU) 2015/830)

APSA GREASE MOLY

Version: 9 **Revision date: 25/07/2018** Print date: 29/11/2018

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

| Name | Bioaccumulation | | | |
|-----------------------------------|-----------------|-----|-------|--------|
| Name | Log Pow | BCF | NOECs | Level |
| triphenyl phosphate | 4,59 | _ | _ | High |
| CAS No: 115-86-6 EC No: 204-112-2 | 7,35 | _ | _ | riigii |

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

Waste classification according to the European Waste Catalogue:

16 WASTES NOT OTHERWISE SPECIFIED IN THE LIST

16 03 off-specification batches and unused products

Page 7 of 9

(in accordance with Regulation (EU) 2015/830)

APSA GREASE MOLY



16 03 06 organic wastes other than those mentioned in 16 03 05

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6. **14.1 UN number.**

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR: Transportation is not dangerous. IMDG: Transportation is not dangerous.

ICAO/IATA: Transportation is not dangerous.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Classification codes:

Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic $\bf 1$: Chronic effect to the aquatic environment, Category 1

(in accordance with Regulation (EU) 2015/830)

APSA GREASE MOLY

Version: 9 Revision date: 25/07/2018



Page 9 of 9 Print date: 29/11/2018

Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3 $\,$

Repr. 2: Reproductive toxicant, Category 2

Sections changed compared with the previous version:

1,3,8,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used: BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration. PPE: Personal protection equipment. LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

Log Pow: Logarithm of the partition octanol-water. NOEC: No observed effect concentration.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.