

LUBRICANTES PARA MOTOR VEHICULO PESADO DIESEL



PRODUCTO	VISCOSIDAD	ACEA	API	MB	VOLVO	MAN	MACK	RENAULT R.V.I	DAF	MTU	OTROS	SISTEMA DE TRATAMIENTO DE GASES
SINTETICOS												
UHPD TLS	10W-40	E6/E7	CI-4	228.51/228.5	VDS 3	M-3271-1/3477	EO-N	RLD2		Type 3.1	CUMMINS CES 20076/20077, DEUTZ DQC III-10	DPF, EGR, SCR
UHPD TLS	5W-30	E4/E6/E7/E9	CJ-4	228.51/228.31	VDS4	M3677/M3477/ M3575/M3271-1	EO-O PP	RLD-3		Type 3.1	SCANIA Low Ash/DEUTZ DQC IV-10LA/CAT ECF-3/ CUMMINS CES 20081/DETROIT DIESEL 93K218	
UHPD	10W-40	E4/E7	CF	228.5	VDS 3	M-3277		RXD/RLD2			SCANIA LDF-3/ LDF 2, IVECO	ALGUNOS MOTORES CON EGR, SCR
UHPD	5W-30	E7/ E4	CI-4	228.5	VDS 3	M-3277 / M3377	EO-M+	RLD2		Type 3	CAT ECF-2 DEUTZ DQC IV-10	EGR, SCR
LANDER PLUS SINT	10W30	E9	CJ-4	228.31	VDS-4	M-3575	EO-O Premium Plus	RLD-3		Type 2.1	CATERPILLAR ECF-3, ECF-2, ECF 1A, CUMMINS CES 20081 , DEUTZ DQC III-10LA	DPF, EGR, SCR
MINERALES												
LANDER PLUS	15W40	E9	CJ-4/SM	228.31	VDS-4	M-3575	EO-O Premium Plus	RLD-3		Type 2.1	CATERPILLAR ECF-3, ECF-2, ECF 1A, CUMMINS CES 20081 DETROIT DIESEL93K218, DEUTZ DQC III-10LA	DPF, EGR, SCR
LANDER	15W-40	E7/E5/E3/B3	CI-4/CH-4/SL	228.3	VDS 3	M-3275-1	EO-N	RLD-2		Type 2	DEUTZ DQC III-10/CAT ECF-1a, ECF2	EGR, SCR
SHPD	15W-40	E5/E3	CH-4/SJ	228.1		M-3275		RD		Type 2		
DIESEL TURBO	15W-40	E2/B2	CF-4/SG	228.1		M-271					VW 505.00	

Nota: Antes de utilizar un aceite se deben comprobar las especificaciones requeridas por el fabricante en el libro de mantenimiento del vehículo